

BRIGHTSTONE NERO

CORRECTIVE IMPREGNATOR
FOR MARBLE AND BLACK SLATE



PACKAGING

1 lt tin – box 6 pc
5 lt tank – box 4 pc.

YIELD

Depending on the absorption of the stone:

- on absorbent stones or with a coarse finish 1lt/8-15 m²;
- on compact stones 1 lt / 15-30 m².

TECHNICAL DATA

Physical state: black liquid

Specific weight (g / cm³) at 20 ° C:
0.82

pH: n.d.

Flame point (ASTM): 43 ° C

Solubility in water: not soluble

Drying time: 8 - 12 hours depending on the ventilation of the rooms

Consolidation time: 24 hours.

STORAGE

Keep the product well closed and at a temperature between 5 and 30 ° C in an aired environment and away from heat sources. If stored at low temperatures (<10 ° C) the product may become dense, but without affecting its use or performance. The product thus stored has a useful life of 5 years.

NOTES

Our indications are based on current research knowledge and are intended to give the best indications to the buyer-user. However, these indications require preliminary examinations and tests on the fields of use, the types of materials present and the various application conditions. The user decides independently on the suitability and on the field of use. MARBECC Srl assumes no responsibility for the incorrect use of its products. **Rev5-Ver241018**

DESCRIPTION

oleo-waxy dispersion in aliphatic paraffinic solvent, modified siccativ oil, mineral microcrystalline wax, resin, lead-free siccativ metal salts, black pigment.

FIELDS OF APPLICATION

Specific for black slate (blackboard) and other black marbles, for indoor and outdoor surfaces..

CHARACTERISTICS

BRIGHTSTONE NERO is a black protective anti-stain impregnator for the color correction of black slates, bleached with acid solutions or degradation due to atmospheric agents and calcareous encrustations.

BRIGHTSTONE NERO:

- Does not form superficial films;
- Does not exfoliate or create peelings;
- Can be used on all surfaces both inside and outside.

INSTRUCTIONS FOR USE

Shake well before use. Apply only on dry surfaces. Distribute **BRIGHTSTONE NERO** with fleece spreader or soft cloth, homogeneously wetting the surface, following the absorption of the stone. After about 10-15 minutes remove any excess product from the surface, rubbing it with a rag or soft disk. It dries after 6-8 hours. On highly absorbent materials, the application of two coats of product may be necessary.

LIMITATIONS

do not accumulate rags, sponges, sawdust, etc., soaked in **BRIGHTSTONE NERO** due to the danger of self-ignition! Dispose of them by wetting them well with water.

WARNING: DANGER



Hazard statements: Flammable liquid and vapour. - May be fatal if swallowed and enters airways. - May cause drowsiness or dizziness. - Repeated exposure may cause skin dryness or cracking. - Contains: Cobalt(II) 2-ethylhexanoate solution. May produce an allergic reaction.

Precautionary statements: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. - Do NOT induce vomiting. - Wear protective gloves / eye protection / face protection. - Avoid breathing dust / fume/ gas/ mist/ vapours/ spray. -Call a POISON CENTER/ doctor/...if you feel unwell. - Store in a well ventilated place. Keep container tightly closed.

Contains: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics. Solvent naphtha 100/ROA.

VOC (Directive 2004/42/CE): VOC fixing primers expressed in g / liter of product ready to use: 750.00 (2010) - Product VOC: 575.00



MARBECC SRL

Via Croce Rossa 5/i
51037 – Montale (PT)
Italy

UNI EN ISO 9001:2008



SISTEMA DI GESTIONE
QUALITÀ CERTIFICATO

CUSTOMER SERVICE

Tel +39 0573 959848

Whatsapp +39 334 857 8502

Email contatti@marbec.it