

# IDROFIN LUCIDO

SHINY ANTI-DIRT ANTI-WEAR FINISHER  
WATER-BASED FOR STONE MATERIALS



## DESCRIPTION

O / W emulsion based on mineral waxes and acrylic-styrene emulsions.

## FIELDS OF APPLICATION

**For the final shiny finish of treatments on absorbent stone materials placed inside:**  
cotto, brick, natural stone with high absorption, cement, mineral plaster.

## CHARACTERISTICS

### IDROFIN:

- is a low-film anti-dirt and anti-wear finisher for absorbent stone materials placed inside;
- protects the hydro-oil repellent protectors from wear;
- does not alter the appearance of the material and does not form a thick film on the surface, leaving a good vapor permeability to the material;
- it forms on the material a resin-waxy micro-layer easy to apply, which reduces the penetration of dirt and makes the surfaces easier and faster to clean;
- easy to maintain over time with the REFIX LUCIDO maintenance product.

## INSTRUCTIONS FOR USE

normally it is used pure. Shake well before use

Application types:

- 1 hand: on smooth and poorly absorbent surfaces;
- 2 hands: on rough surfaces.

The product is distributed with fleece wax spreader, soft cloth or sponge. It should be spread in a thin layer, homogeneously wetting the surface and without making excesses. It dries quickly, generally in 2-3 hours in well-ventilated areas. Apply the second coat as soon as the first one is dry.

## LIMITATIONS

- avoid application by paint brush or roller. Do not use outside.
- avoid applying **IDROFIN** on surfaces that are too cold (<5 °C)
- in the cleaning of surfaces treated with **IDROFIN**, avoid using strong alkaline and acid detergents (eg ammonia, sodium hypochlorite, various acids) and solvents (eg ethyl alcohol).

## PACKAGING

1 lt plastic bottle – box 6 pc;  
5 lt plastic can – box 4 pc;  
20 lt plastic can.

## YIELD

Depending on the absorption of materials.

- on materials with rough surfaces 1 lt / 10-18 m<sup>2</sup>;
- on materials with polished surfaces 1 lt / 20-30 m<sup>2</sup>.

## TECHNICAL DATA

Physical state: white liquid  
Specific weight (g / cm<sup>3</sup>): 1  
pH: 8  
Flame point (ASTM): non-flammable  
Solubility in water: total  
Drying time: 2 - 3 hours  
Consolidation time: 24 hours

## STORAGE

Keep the product well closed at temperatures between 0 °C and + 30 °C). The product thus conserved has a useful life of 2 years.

## NOTES

Our indications are based on current research knowledge and are intended to give the best indications to the buyer-user. However, these indications require preliminary examinations and tests on the fields of use, the types of materials present and the various application conditions. The user decides independently on the suitability and on the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products. **Rev2-Ver010218**

## WARNING: CAUTION

**Precautionary statements:** Safety data sheet available on request.

VOC (Directive 2004/42/EC) : One-pack performance coatings.  
VOC given in g/litre of product in a ready-to-use condition : Limit value: 140,00 (2010)  
VOC of product : 22,00.



MARBEC SRL

Via Croce Rossa 5/i  
51037 – Montale (PT)  
Italy

UNI EN ISO 9001:2008



SISTEMA DI GESTIONE  
QUALITÀ CERTIFICATO

## CUSTOMER SERVICE

Tel +39 0573 959848  
Whatsapp +39 334 857 8502  
E-mail [contatti@marbec.it](mailto:contatti@marbec.it)