

BRIGHTSTONE

TONING IMPREGNATOR
FOR STONE MATERIALS



PACKAGING

1 lt tin – box 6 pc
5 lt tank – box 4 pc.

YIELD

- on absorbent stones or with a coarse finish 1lt/8-15 m²;
- on compact stones 1 lt / 15-30 m².

TECHNICAL DATA

Physical state: clear liquid from violet-
ceo to brown
Specific weight (g / cm³) at 20 ° C:
0.82
pH: n.d.
Flame point (ASTM): 43 ° C
Solubility in water: not soluble
Drying time: 8 - 12 hours depending
on the ventilation of the rooms
Consolidation time: 24 hours.

STORAGE

Keep the product well closed and at a
temperature between 5 and 30 ° C in
an aired environment and away from
heat sources. If stored at low temper-
atures (<10 ° C) the product may be-
come dense, but without affecting its
use or performance. The product thus
stored has a useful life of 5 years.

NOTES

Our indications are based on current research
knowledge and are intended to give the best indi-
cations to the buyer-user. However, these indica-
tions require preliminary examinations and tests on
the fields of use, the types of ma-terials present and
the various application conditions. The user decides
independently on the suitability and on the field of
use. MARBEC Srl assumes no responsibility for the
incorrect use of its products. **Rev5-Ver241018**

DESCRIPTION

Oily-waxy dispersion in aliphatic paraffinic solvent based on drying oils, mineral microcrystalline wax, and lead-free metal salts.

FIELDS OF APPLICATION

specific for the impregnating toning treatment of low absorption stones (slate, granite, porphyry, marble, etc.), polished grits and cotto. On all stone surfaces inside and outside.

CHARACTERISTICS

BRIGHTSTONE is an anti-stain protective toning impregnator specific for: low absorption stones (slate, granite, porphyry, marble, etc.), polished grits and cotto.

BRIGHTSTONE:

- **Does not form superficial films;**
- **Does not exfoliate or create peelings;**
- **Can be used on all surfaces both inside and outside.**

INSTRUCTIONS FOR USE

Shake well before use. Apply only on dry surfaces. Distribute **BRIGHTSTONE** with fleece spreader or soft cloth, homogeneously wetting the surface, following the absorption of the stone. After about 10-15 minutes remove any excess product from the surface, rubbing it with a rag or soft disk. It dries after 6-8 hours. On highly absorbent materials, the application of two coats of product may be necessary. On the most compact materials (marble, travertine, etc.) it may be necessary to dilute **BRIGHTSTONE** with the **DILUOIL** solvent (20-50%). Do not apply the product on surfaces exposed to sunlight and too hot. It can be pigmented with **OILTONER**.

LIMITATIONS

do not accumulate rags, sponges, sawdust, etc., soaked in **BRIGHTSTONE** due to the danger of self-ignition! Dispose of them by wetting them well with water.

WARNING: DANGER



Hazard statements: Flammable liquid and vapour. - May be fatal if swallowed and enters airways. - May cause drowsiness or dizziness. - Repeated exposure may cause skin dryness or cracking. - Contains: Cobalt(II) 2-ethylhexanoate solution. May produce an allergic reaction.

Precautionary statements: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. - Do NOT induce vomiting. - Wear protective gloves / eye protection / face protection. - Avoid breathing dust / fume/ gas/ mist/ vapours/ spray. -Call a POISON CENTER/ doctor/.../if you feel unwell. - Store in a well ventilated place. Keep container tightly closed.

Contains: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics. Solvent naphtha 100/ROA.

Category: VOC fixing primers expressed in g / liter of product ready to use: 750.00 (2010) - Product VOC: 575.00



MARBEC SRL

Via Croce Rossa 5/i
51037 – Montale (PT)
Italy

UNI EN ISO 9001:2008



SISTEMA DI GESTIONE
QUALITÀ CERTIFICATO

CUSTOMER SERVICE

Tel +39 0573 959848
Whatsapp +39 334 857 8502
Email contatti@marbec.it