

# AGRUMOIL

## DEGREASING DILUENT WITH D-LIMONENE FOR WOOD



### DESCRIPTION

mixture of solvents, aliphatic hydrocarbons and D-Limonene.

### FIELDS OF APPLICATION

specific for cleaning all wooden surfaces

### CHARACTERISTICS

#### AGRUMOIL:

- cleans all wooden surfaces dirty with fatty substances or soot;
- makes a superficial de-resination of resinous wood essences;
- is suitable for extraordinary maintenance and recovery of floors treated with deteriorated oil-waxy impregnator;
- it does not leave halos and does not stain the wood essence.

It can be used to dilute the oil-waxy impregnating products (eg TIROIL, OLIO41, OLIO TECNO, FLUOIL, TUSCANIA OIL, WET OUT, OIL WET) and facilitate their absorption in low-absorbent materials.

### INSTRUCTIONS FOR USE

spread **AGRUMOIL** on the surface and let it act for a few minutes. Rub the surface with a mono-brush equipped with a medium-hard disk, buffer or cloth. Remove and collect the residues. Clean the surface with a clean cloth moistened with **AGRUMOIL**.

### LIMITATIONS

- protect all painted surfaces from contact with **AGRUMOIL**.
- **AGRUMOIL** on decorated wooden structures can have an undesired solvent action on the colors of the decoration. Therefore, in these cases, it is advisable to make small preliminary tests.

### PACKAGING

1 lt Tin – box 6 pc;  
5 lt Tank – box 4 pc.

### YIELD

depending on the consistency of the dirt to be removed or the degree of dilution required

### TECHNICAL DATA

Physical state: clear, colorless liquid  
Specific weight (g / cm<sup>3</sup>) at 20 ° C:  
0.782  
pH: n.a.  
Flame point (ASTM): 40 ° C  
Solubility in water: not soluble

### STORAGE

keep the product well closed and at a temperature between 5 and 30 ° C in an aired environment and away from heat sources. If stored at low temperatures (<10 ° C) the product may become dense, but without compromising its use or performance. The product thus conserved has a useful life of 5 years.

### NOTES

*Our indications are based on current research knowledge and are intended to give the best indications to the buyer-user. However, these indications require preliminary examinations and tests on the fields of use, the types of materials present and the various application conditions. The user decides independently on the suitability and on the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products Rev3-Ver050219*

### WARNING: DANGER



**Hazard statements:** Flammable liquid and vapour. - May be fatal if swallowed and enters airways. May cause an allergic skin reaction. - May cause drowsiness or dizziness. - Toxic to aquatic life with long-lasting effects. - Repeated exposure may cause skin dryness or cracking.

**Precautionary statements:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. - Avoid breathing dust/fumes/gas/mist/vapours/spray. - Avoid release to the environment. - Wear protective gloves / protective clothing / eye protection / face protection. - Call a POISON CENTER or doctor/physician if you feel unwell. - Do NOT induce vomiting. - Collect spillage.

**Contains:** Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics < 2% aromatics, d-Limonene.



MARBEC SRL

Via Croce Rossa 5/i  
51037 – Montale (PT)  
Italy

UNI EN ISO 9001:2008



SISTEMA DI GESTIONE  
QUALITÀ CERTIFICATO

CUSTOMER SERVICE

Tel +39 0573 959848  
Whatsapp +39 334 857 8502  
Email [contatti@marbec.it](mailto:contatti@marbec.it)