

BARRIER

PROTECTIVE AND NUTRITIVE
FINISHER FOR OUTDOOR WOOD



PACKAGING

- 1 lt Plastic bottle - box of 6 pcs
- 5 lt Plastic tank - box of 4 pcs.

YIELD

Indicatively 1lt / 30 - 40 m2.

TECHNICAL DATA

Physical state: white opaque liquid
Specific weight (g / cm3): 1
pH: 8
Flash point (ASTM): not in-flammable
Solubility in water: total
Drying time: 30 - 60 minutes
Consolidation time: 24

STORAGE

Keep the product well closed at temperatures between 0 ° C and + 30 ° C). The product thus conserved has a useful life of 2 years.

DESCRIPTION

O / A emulsion based on vegetable waxes, paraffin, fatty acid ester, resin, non-ionic surfactants.

FIELDS OF APPLICATION

on all types of wooden surfaces placed outside treated with transparent varnishes, paints and stains, impregnators, oils (floors, coverings, garden furniture, structures, etc.). Ideal for reviving PVC and painted aluminum windows.

CHARACTERISTICS

BARRIER:

- protects the bottom treatment products from wear and aging over time (e.g. HYDROIL ESTERNO, FLUOIL, OLIO41);
- has excellent resistance to UV rays and atmospheric agents;
- does not alter the appearance of the material and does not form a thick film on the surface, leaving good vapor permeability to the material;
- constitutes an easy-to-apply resin-waxy micro-layer on the material, which increases the water-repellent and anti-stain resistance of the treated surfaces;
- makes surfaces easier and faster to clean;
- can be easily maintained over time with the application of the product at least once a year.

INSTRUCTIONS FOR USE

Shake well before use.

- **On floors and on large surfaces:** spread **BARRIER** with a fleece spreader / sponge / soft cloth and distribute a thin and uniform layer of product avoiding excess. Generally, only one hand of **BARRIER** is enough. Only on non-smooth finish woods (e.g. brushed, aged, sandblasted) a second coat of product can be requested. In summer and in any case in environments with temperatures > 25 ° and ventilated to prevent the finish from drying too quickly, dilute the **BARRIER** with 30% of water. In this case, apply two light coats;

- **On furniture, fixtures, wooden structures, etc.:** apply the product with an absorbent cloth or sponge and distribute a thin and uniform layer of product avoiding excess. Do not let the product rest on wood, especially on woods rich in tannin (ex. Oak, Chestnut, Larch).

Rinse the equipment with water before drying the product. In the hot season or in highly ventilated areas, it can be useful to dilute **BARRIER** 3: 1 in water to facilitate its application.

It generally dries in 1-2 hours.

LIMITATIONS

- Does not apply on painted floors. The use of roller and brush is not recommended.

NOTES

Our indications are based on current research knowledge and are intended to give the best indications to the buyer-user. However, these indications require preliminary examinations and tests on the fields of use, the types of materials present and the various application conditions. The user decides independently on the suitability and on the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products. **Rev2-Ver260318**

WARNING

Hazard classification and indication: safety data sheet available on request.



MARBEC SRL

Via Croce Rossa 5/i
51037 - Montale (PT)
Italy

UNI EN ISO 9001:2008



SISTEMA DI GESTIONE
QUALITÀ CERTIFICATO

CUSTOMER SERVICE

Tel +39 0573 959848
Whatsapp +39 334 857 8502
Email contatti@marbec.it