

# DILUOIL

THINNER FOR OIL-WAX  
IMPREGNATING PRODUCTS



## DESCRIPTION

mixture of denatured aliphatic hydrocarbon solvents.

## FIELDS OF APPLICATION

**solvent for the dilution of oleo-wax impregnating products** and facilitating their absorption in low-porous materials..

## CHARACTERISTICS

### DILUOIL:

- it can also be used to clean all the wooden surfaces soiled with greasy substances or with soot and to do a superficial de-resination of resinous wood essences;
- it is indicated for the dilution of oil-wax impregnating products such as TIROIL, OLIO TECNICO, FLUOIL, OLIO 41, TUSCANIA OIL, WET OUT, OIL WET;
- it is indicated for extraordinary maintenance and recovery of floors treated with deteriorated oleo-wax impregnators;
- it is a mixture of solvents with low danger for humans and the environment;
- does not leave halos and does not stain the wood essence.

## INSTRUCTIONS FOR USE

Do not apply the product on surfaces exposed to the sun and too hot. It can be pigmented with **OILTONE**. As a diluent it can be used in all concentrations.

In extraordinary cleaning, spread **DILUOIL** on the surface and let it act for a few minutes. Rub the surface with a monobrush equipped with a medium-hard disk, pad or rag. Remove and collect residues. Clean the surface with a clean cloth damp with **DILUOIL**.

## LIMITATIONS

- protect all painted surfaces from contact with **DILUOIL**;
- the product, especially on decorated wooden structures, may have an undesirable solvent action on the colors of the decoration. Therefore, in these cases, it is advisable to make small preliminary tests.

## PACKAGING

1 lt Tin- box 6 pc;  
5 lt Tank - box 4 pc.

## YIELD

according to the consistency of the dirt to be removed or the desired degree of dilution.

## TECHNICAL DATA

Physical state: clear colorless liquid  
Specific weight (g / cm<sup>3</sup>) at 20 ° C:  
0.771  
pH: n.a.  
Flash point (ASTM): 40 ° C  
Solubility in water: not soluble.

## STORAGE

keep the product well closed and at a temperature between 5 and 30 ° C in an aired environment and away from heat sources. If stored at low temperatures (<10 ° C) the product may become dense, but without compromising its use or performance. The product thus conserved has a useful life of 5 years.

## NOTES

Our indications are based on current research knowledge and are intended to give the best indications to the buyer-user. However, these indications require preliminary examinations and tests on the fields of use, the types of materials present and the various application conditions. The user decides independently on the suitability and on the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products. **Rev4-Ver080219**

## WARNING: DANGER



**Hazard statements:** Flammable liquid and vapour. - May be fatal if swallowed and enters airways. - May cause drowsiness or dizziness. - Repeated exposure may cause skin dryness or cracking.

**Precautionary statements:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. - Avoid breathing dust /fume /gas /mist /vapours /spray. - Wear protective gloves / clothing and eye / face protection. - IF SWALLOWED: Call a POISON CENTER or doctor / physician if you feel unwell. - IF INHALED: Remove person to fresh air and keep comfortable for breathing. - Do NOT induce vomiting.

**Contains:** Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics.



MARBEC SRL

Via Croce Rossa 5/i  
51037 - Montale (PT)  
Italy

UNI EN ISO 9001:2008



## CUSTOMER SERVICE

Tel +39 0573 959848  
Whatsapp +39 334 857 8502  
Email [contatti@marbec.it](mailto:contatti@marbec.it)