

BIOTOP

ANTI-DIRT, ANTI-WEAR
FINISHER FOR WOOD



DESCRIPTION

O / A emulsion based on vegetable waxes, paraffin, fatty acid ester, resin, non-ionic surfactants.

FIELDS OF APPLICATION

on all types of wooden surfaces placed inside (parquet, planks, furniture, tables, beams and wooden structures in general).

CHARACTERISTICS

Specific finisher for oil-wax impregnation products of wood: **OLIO TECNO, TIROIL, OLIO ZERO, HYDROIL**. It integrates and completes the water-repellent, anti-stain and anti-dirt protection giving the wooden surface easy to clean and renew, therefore making maintenance especially on the floor easy and practical.

BIOTOP:

- protects the impregnating products from the effects of time;
- is a product formulated in water. It does not leave unpleasant odors in the rooms;
- does not alter the appearance of the material and does not form a thick film on the surface, leaving a good vapor permeability to the material;
- it is an easy-to-apply, resin-waxy micro-layer on the material, which reduces the penetration of dirt and makes the surfaces easier and faster to clean;
- easy maintenance over time with the **BIOCARE** maintenance product.

PACKAGING

1 lt plastic bottle – box 6 pc
5 lt plastic tank – box 4 pc

YIELD

Indicatively 1lt/ 30 - 40 m².

TECHNICAL DATA

Physical state: white opaque liquid
Specific weight (g / cm³): 1
pH: 8
Flash point (ASTM): non-flammable
Solubility in water: total
Drying time: 30 - 60 minutes
Consolidation time: 24 hours

STORAGE

Keep the product well closed at temperatures between 0 ° C and + 30 ° C). The product thus conserved has a useful life of 2 years.

INSTRUCTIONS FOR USE

Shake well before use.

- **On floors and large surfaces:** spread **BIOTOP** with fleece wax spreader / sponge / soft cloth and distribute a thin and uniform layer of product avoiding excesses. It is sufficient, generally only one coat of **BIOTOP**. Only on non-smooth finish woods (eg brushed, aged, sanded) a second coat of product may be required. In this year and in any case in environments with temperatures > 25 ° and ventilated to prevent the finish from drying too quickly, dilute the **BIOTOP** with 30% of water. Apply two light coats in this case;
- **On furniture, fixtures, wooden structures, etc.:** apply the product with absorbent cloth or sponge and distribute a thin and uniform layer of the product avoiding excesses. Do not let the product stagnate on the wood, especially on woods rich in tannins (eg Oak, Chestnut, Larch). Rinse the equipment with water before the product dries. In hot weather or in very ventilated areas it may be useful to dilute **BIOTOP** 3: 1 in water to make it easier to apply. Dry generally in 1-2 hours.

LIMITATIONS

Does not apply to painted floors. Use of roller and brush is not recommended.

NOTES

Our indications are based on current research knowledge and are intended to give the best indications to the buyer-user. However, these indications require preliminary examinations and tests on the fields of use, the types of materials present and the various application conditions. The user decides independently on the suitability and on the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products. **Rev2-Ver130318**
Rev3-Ver260318

WARNINGS

Hazard statements: safety data sheet available on request.



MARBEC SRL

Via Croce Rossa 5/i
51037 – Montale (PT)
Italy

UNI EN ISO 9001:2008



SISTEMA DI GESTIONE
QUALITÀ CERTIFICATO

CUSTOMER SERVICE

Tel +39 0573 959848
Whatsapp +39 334 857 8502
Email contatti@marbec.it