

OLIO ZERO

ULTRA-OPAQUE IMPREGNATING OIL FOR WOOD



PACKAGING

-1 Kg PE container - box 6 pcs
-5 Kg PE container - box 4 pcs

YIELD

in three steps: 1 kg/6-8 m²;
(with roll 125-160 g/m²).

TECHNICAL DATA

Physical state: white viscous liquid
Specific weight (g / cm³) at 20 ° C:
1.055
pH: 7
Flame point (ASTM): > 100C °
Solubility in water: total
Drying time: 30-60 min.
Sandability time: 2-3 hours
Curing time: 24 hours
Gloss: <5 (ultra-opaque)

STORAGE

Keep the product well closed at temperatures between 0 ° C and + 30 ° C). The product thus conserved has a useful life of 2 years.

DESCRIPTION

PU impregnating emulsion based on oils, resins, waxes and special inert additives.

FIELDS OF APPLICATION

For the impregnating treatment of all rough wooden surfaces placed inside (flooring, coverings, wooden structures, furniture, doors and windows).

CHARACTERISTICS

OLIO ZERO:

- is particularly indicated to obtain a "natural effect" wood protection which preserves the original aesthetic characteristics of the raw wood (ultra-opaque finish) and is practically invisible;
- is a product with a low content in VOC (volatile compounds), ecological and easy to use;
- gives to the wooden surface a non-yellowing, anti-slip, stain and dirt resistant finish and it's easy to maintain over time with BIOCARE OPACO.

INSTRUCTIONS FOR USE

Mix **OLIO ZERO** well before use it. Do not dilute. The wood must be clean, well sanded (100-150 paper) and free of old residual films. The product can be applied with a brush or with a short-haired roller "wet on wet" in order to avoid overlapping. Three hands of **OLIO ZERO** are always necessary except on the ceiling wood where it can be applied in two steps. When the first coat is dried (1-2 hours) the second coat is applied proceeding as for the previous one. When the latter is also dry (2-4 hours), it is possible to lightly sand it with 180-240 grain and after having removed the powder, apply the third coat of product. The product is hardened and can be walked on after 24 hours.

NOTES

Our indications are based on current research knowledge and are intended to give the best indications to the buyer-user. However, these indications require preliminary examinations and tests on the fields of use, the types of materials present and the various application conditions. The user decides independently on the suitability and on the field of use. MARBEC Srl assumes no responsibility for the incorrect use of its products. **Rev3-Ver150219**

WARNING:

Hazard statements: Safety data sheet available on request. - Contains: 1,2-benzisotiazol-3(2H)-one. May cause an allergic reaction.

VOC (Directive 2004/42 /EC): Wood varnishes and impregnating agents for interior / exterior finishes.
VOC expressed in g / liter of product ready to use: Maximum limit: 130.00 (2010) - VOC of the product: 90.00.



MARBEC SRL

Via Croce Rossa 5/i
51037 – Montale (PT)
Italy

UNI EN ISO 9001:2008



SISTEMA DI GESTIONE
QUALITÀ CERTIFICATO

CUSTOMER SERVICE

Tel +39 0573 959848
Whatsapp +39 334 857 8502
Email contatti@marbec.it